What is claimed is:

| 1 | 1. A gasket for sealing duct sections, comprising: |
|---|--|
| 2 | a sealing ring having a base portion for receiving an end of an inner duct |
| 3 | section or connector to be joined, and a substantially J-shaped cross- |
| 4 | section; and |
| 5 | a flexible hollow sealing portion of substantially circular cross-sectional shape |
| 6 | affixed to said base portion and protruding in a radially outward |
| 7 | direction, for engagement with an outer duct section or connector to be |
| 8 | joined. |
| 1 | 2. The gasket of claim 1, wherein said base portion also includes a lip protruding in a radially |
| 2 | inward direction for engagement with a complimentary groove or depression on said |
| 3 | inner duct section or connector to be joined. |
| 1 | 3. The gasket of claim 1, wherein said base portion and said flexible hollow sealing portion |
| 2 | comprise materials having a different hardness. |
| 1 | 4. The gasket of claim 3, wherein said base portion is harder than said flexible hollow sealing |
| 2 | portion. |
| 1 | 5. The gasket of claim 1, wherein said base portion is removably fitted onto an unrolled or |
| 2 | unfolded edge of said inner duct section or connector. |
| 1 | 6. The gasket of claim 1, wherein said base portion is permanently secured onto an unrolled or |
| 2 | unfolded edge of said inner duct section or connector. |
| 1 | 7. The gasket of claim 2, wherein said base portion and said flexible hollow sealing portion |
| 2 | comprise materials having a different hardness. |
| 1 | 8. The gasket of claim 7, wherein said base portion is harder than said flexible hollow sealing |
| 2 | portion. |
| 1 | 9. The gasket of claim 7, wherein said base portion is removably fitted onto an unrolled or |
| 2 | unfolded edge of said inner duct section or connector. |

- 1 10. The gasket of claim 7, wherein said base portion is permanently secured onto an unrolled 2 or unfolded edge of said inner duct section or connector.
- 1 11. The gasket of claim 8, wherein said base portion is removably fitted onto an unrolled or unfolded edge of said inner duct section or connector.
- 1 12. The gasket of claim 8, wherein said base portion is permanently secured onto an unrolled 2 or unfolded edge of said inner duct section or connector.